

RIGID CULTIVATOR

STANDARD DUTY

LANDFORCE



Robust Frame

75x40x5 Channel Frame



Forged Tynes

50x25 Forged Tynes



Power-Matched Performance

40-50-60 HP required



Tyne Spacing

9 Inch



Cat-II Hitch

Robust connection for seamless operation



Efficient Operation

Consistent field performance



RIGID CULTIVATOR

Standard Duty

Rigid Cultivator Standard Duty is an agricultural tool designed to help farmers cultivate soil, control weeds, and aerate the ground. The heavy duty frame designed refers to the best quality of the machine. The tines are typically used to break up the soil without damaging it.



TECHNICAL SPECIFICATIONS

MODEL	Unit	LFCSR7	LFCSR9	LFCSR11	LFCSR13
Frame	mm	Pipe 72x72x6			
Working Width	mm	1435	1900	2350	2810
Length	mm	1550	2010	2460	2914
Width	mm	675			
Height	mm	1160			
No. of Tynes/Shovel	No.	7	9	11	13
Tyne Type		50x25 Forged			
Tyne Spacing	inch/mm	9" / 228 mm			
Hitch Category		CAT-II			
Min Hp Required	hp	35	40	45 to 55	60
Weight	kg	150	195	230	265

**Company reserves the rights to change/amend products specifications without any prior notice.*