

MOULD BOARD PLOUGH

REVERSIBLE

LANDFORCE



Tractor Compatibility
50-90 hp above
Weight: 470 kg



Versatile Frame & Rugged Frame
2, 3 or 4 Furrow options
Heavy Duty 95x95x8 mm



Boron Steel Tynes
Profile cut for unmatched durability & soil penetration



Durable Mould Board
Thick 8 mm
Mould Board



Standard Cat-II Hitch
Adjustable Depth of cut
250-400 mm



Integrated Support Wheel
Optional/Provided for depth and stability



MOULD BOARD PLOUGH

Reversible

A robust designed of Landforce Reversible MB plough agricultural implement used for turning the soil levels upside down, incorporating soil reduces and making available more fertile layer for the new crop. It provides deep seed bed preparation with proper aeration and efficient residue incorporation. MB Plough is used as a primary tillage implement for soft and hard soils.



Depth control wheel for efficient ploughing



TECHNICAL SPECIFICATIONS

MODEL	Unit	LFRMBF2	LFRMBF3	LFRMBF4
No. Of Furrows	No.	2	3	4
Frame		95x95x8		
Draw Bar Rod		40		
Tyne Type		Profile Cut Boron Steel		
Length	mm	2210	3015	3780
Width	mm	1125	1480	1825
Height	mm	1540		
Mould Board (Thickness)	mm	8		
Hitch Type		CAT-II		
Width Of Cut	mm	865	1250	1635
Depth Of Cut	mm	250-400		
Support Wheel		Optional	Provided	
Tractor Req.	hp	50-75	75-90	90 Above
Weight	kg	470	635	800

*Company reserves the rights to change/amend products specifications without any prior notice.