MOUNTED DISC HARROW

STANDARD DUTY



Tractor HP Required
30to100 hp

Versatile Model Range
LFDHSM12-
LFDHSM24

Durable Boron Steel Discs
22 inch
Front notched
rear plain

Multiple Disc Options
12 to 24 Discs

Working Width
1415-2720 mm

Reinforced Angle Frame
75x10

MOUNTED DISC HARROW

Standard Duty

LANDFORCE Mounted Disc Harrow is designed for efficient soil cutting, mixing, and field preparation in tough farming conditions. Its heavy-duty discs ensure deeper penetration and smooth operation for better seedbed preparation. Built with a strong and durable frame for long-lasting performance and higher productivity.



Compatible as per CAT-II specifications ensures versatility

Front notched disc and Rear plain disc





TECHNICAL SPECIFICATIONS

MODEL	Unit	LFDHSM12	LFDHSM14	LFDHSM16	LFDHSM18	LFDHSM20	LFDHSM22	LFDHSM24
Frame		Angle 75x10						
No. of Disc	No.	12	14	16	18	20	22	24
Disc Type		Boron Steel, Front notched & rear plain discs						
Disc Size	inch	22"						
Working Width	mm	1415	1640	1850	2070	2285	2500	2720
Disc Spacing	mm	228						
No. of Bearing hubs	No.	4		8				
Overall Length	mm	1670	1855	2040	2000	2450	2460	2685
Overall Width	mm	1950	1940	2025	2300	2555	2885	2920
Overall Height	mm	1255						
Tractor HP Req.	hp	30-40	40-50	50-60	60-70	70-80	80-90	90-100
Weight	kg	410	450	530	600	645	710	750

**Company reserves the rights to change/amend products specifications without any prior notice.*