POWER HARROW

RHINO (STANDARD)



Heavy-Duty Construction
Built with a robust frame for long-lasting durability

Working Width
1000-3000 mmm

Working Depth
Up to 280 mm

Multiple Blade Configuration
8 to 32 Blades

PTO Safety System
Slip clutch and drive shaft protection

Roller System
Packer or cage roller option

POWER HARROW

Rhino (Standard)


Landforce Power Harrow is suitable for the crops which required deeper tillages like Potato & Tuber crops. Its boron steel long blades help achieve deep tillage in any type of soil. It reduces the number of tillage operations reducing number of passes, thus help in reducing compaction of soil. It comes with multispeed. The levelling bar is a standard feature and accessories consist of three type of Rollers: Packer roller, Spike roller & Cage roller.



Compatible as per CAT-II specifications ensures versatility



High Quality Boron Steel Verticle Blades for more depth & better pulverization best for hard soil



Heavy duty Gearbox



TECHNICAL SPECIFICATIONS

MODEL	Unit	LFPHS100	LFPHS125	LFPHS150	LFPHS175	LFPHS200	LFPHS225	LFPHS250	LFPHS275	LFPHS300
Type		Standard Duty								
Length	mm	1115	1400	1645	1855	2100	2345	2590	2835	3080
Width	mm	1501								
Height	mm	1210								
Working Width	mm	1000	1230	1500	1750	2000	2250	2500	2750	3000
Max Working Depth	mm	280								
Blades	No.	8	10	12	14	16	18	20	22/28	24/32
Blade Dimantion	mm	285(L)x12(T)								
PTO Speed	rpm	540/1000								
3 Point Linkage		CAT-II								
PTO Safety Device		Slip clutch / Driveshaft W / Automatic clutch (opt.)								
Leveling Bar		Provided (Mechanical Type)								
Roller Type		Packer Roller/Cage Roller								
Packer Roller Dia	mm	450								
Cage Roller Dia	mm	360								
Roller Adjustment		Auto/Pin Type/Hydraulic								
Transmission Type		Gear								
Tractor HP Req.	hp	45-60	55-70	60-75	65-80	70-85	75-90	80-95	85-110	90-115
Weight W/o Roller	kg	465	515	565	810	855	905	1055	1090/1260	1150/1370

**Company reserves the rights to change/amend products specifications without any prior notice.*